



Republic of the Philippines
BULACAN AGRICULTURAL STATE COLLEGE
REQUEST FOR QUOTATION

Document No.: BASC-PRO-QSF-02
 Rev. No.: 00
 Effectivity Date: 06/03/2019

Project Reference Number:
 Name of the Project:
 Location of the Project:

Date: _____
 Quotation No. _____

Company Name _____
 Address _____

Please quote your lowest price on the item/s listed below, subject to the General Conditions on the last page, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than _____ in the return envelope attached herewith.

MANDY D. BERNARDO
 Procurement Officer

- NOTE:
1. THE APPROVED BUDGET FOR THE CONTRACT IS _____.
 2. ALL ENTRIES MUST BE TYPEWRITTEN.
 3. DELIVERY PERIOD WITHIN _____ CALENDAR DAYS.
 4. WARRANTY SHALL BE FOR A PERIOD OF three (3) MONTHS FOR NON-EXPENDABLE SUPPLIES ONE (1) YEAR NON-EXPENDABLE SUPPLIES FROM DATE ACCEPTANCE BY THE PROCURRING ENTITY.
 5. PRICE VALIDITY SHALL BE FOR A PERIOD OF _____ CALENDAR DAYS.
 6. PHILGEPS REGISTRATION CERTIFICATE SHALL BE ATTACHED UPON SUBMISSION OF THE QUOTATION.
 7. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATION OF THE PRODUCT BEING OFFERED.

ITEM No.	Unit	ITEM & DESCRIPTION	QTY	UNIT PRICE	TOTAL
1	set	FULL HD 1080p PTZ CAMERA 30X POE With PTZ Camera Controller 1/2.8" HD CMOS Sensor, 20X/30X Optical Zoom HDMI & 3G-SDI Video Output, PoE Power RS-232/RS-485 Serial Control, Cascading Streaming Protocols: RTSP, RTMP, SRT Control Protocols: Onvif, VISCA over IP, VISCA, PELCO-D/P Tripod, Wall & Ceiling Mounting	1		
		PTZ CAMERA JOYSTICK CONTROLLER Control protocol by VISCA, VISCA-Over-IP, Onvif and Pelco P&D Control up to total of 255 IP cameras on a single network 6 camera quick call up keys, and 6 user-assignable keys to quickly invoke shortcut functions Quick control of exposure, shutter speed, iris, compensation, white balance, focus, pan/tilt speed, zoom speed Tactile feel with professional rocker/seesaw switch for zoom control Automatically search available IP cameras in a network and assign IP addresses easily Tally GPIO output for indicating the camera be currently controlled Metal housing with 2.2 inch LCD display, 4D joystick, 5 rotation button Supports both POE and 12V DC power supplies			
2	unit	TRIPOD WITH CARRYING BAG Tripod Sections: 4 Diameter range: 14/23mm Maximum height: 1630mm Does not rise axis height: 1300mm Minimum height: 535mm Storage Height: 550mm Load bearing: 4KG	3		
3	unit	4 CHANNEL HDMI/ DP VIDEO SWITCHER Inputs 1~3: HDMI, Input 4: HDMI/DP Outputs: HDMI PGM×2, HDMI multiview×1, USB type-C×1, LAN×1 LAN port for RTMP streaming and upgrade USB disk/ SD card for PGM recording USB Type-C for video capturing (UVC) PIP function, adjustable size and position Audio mixer: 3.5mm MIC/ RCA/ HDMI embedded audio AUTO/ CUT transitions and MIX/ FADE/ WIPE effects GPIO interface for live tally system FTB for emergency situation	1		
4	pc	HDMI Cable 10m	3		

Brand and Model _____
 Delivery Period: _____
 Warranty: _____
 Price Validity: _____

After having carefully read and accepted your General Conditions, I/We quote on the item at prices noted above.

Printed Name / Signature

Tel. No. / Cellphone No.
 e-mail address

Date