Republic of the Philippines

BULACAN AGRICULTURAL STATE COLLEGE

REQUEST FOR QUOTATION

Document No.: BASC-PRO-QSF-02 Rev. No.: 00

Effectivity Date: 06/03/2019

Project Reference Number: Name of the Project: Location of the Project:

	Date: Quotation No.
Company Name	
Address	
Please quote your lowest price on the item/s listed below, subject to the General	ral Conditions on the
last page, stating the shortest time of delivery and sumbit your quotation duly signed by y	your representative not later than
in the return envelope attached herewith.	
	MANDY D. BERNARDO
	Procurement Officer
A WILL A DED OUTD DUD COM FOR MUT GOLDEN A CW IC	

- 1. THE APPROVED BUDGET FOR THE CONTRACT IS _
- 2. ALL ENTRIES MUST BE TYPEWRITTEN.
- 3. DELIVERY PERIOD WITHIN _____ CALENDAR DAYS.
- 4. WARRANTY SHALL BE FOR A PERIOD OF three (3) MONTHS FOR NON-EXPENDABLE SUPPLIES ONE (1) YEAR NON-EXPENDABLE SUPPLIES FROM DATE ACCEPTANCE BY THE PROCURRING ENTITY.
- 5. PRICE VALIDITY SHALL BE FOR A PERIOD OF ___ __ CALENDAR DAYS.
- 6. PHILGEPS REGISTRATION CERTIFICATE SHALL BE ATTACHED UPON SUBMISSION OF THE QUOTATION.
- 7. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATION OF THE PRODUCT BEING OFFERED.

ITEM No.	Unit	ITEM & DESCRIPTION	QTY	UNIT PRICE	TOTAL
1	Lot	Radio Broadcasting Set	1		
		AIO PC		-	-
		Operating system: Genuine Windows 11 Home			
		Processor: AMD Ryzen™ 7 5825U (up to 4.5 GHz max boost clock, 16 MB L3 cache, 8 cores,		-	
		16 threads)			
				-	
		Graphics: Integrated: AMD Radeon™ Graphics Display 27" diagonal, FHD (1920 x 1080), touch, IPS			
		Memory: 16 GB DDR4-3200 MHz RAM (2 x 8 GB)		-	
		Storage: 512 GB PCIe® NVMe™ M.2 SSD		+	
		Secondary storage: 1 TB 5400 rpm SATA HDD		-	
		Network interface: Integrated 10/100/1000 GbE LAN		-	
				-	
		Wireless technology: Realtek Wi-Fi 6 (2x2) and Bluetooth® 5.3 wireless card (supporting gigabit		+	
		data rate)		+	
		Power supply: 120 W Smart AC power adapter		+	
		External I/O Ports:		+	
-		Rear : 1 USB Type-C® 5Gbps signaling rate;		+	
		1 USB Type-A 5Gbps signaling rate; 2 USB 2.0		 	
		Type-A; 1 RJ-45		+	
	***************************************	Side : 1 USB Type-A 5Gbps signaling rate (Battery		+	
		Charging 1.2); 1 headphone/microphone combo		-	
		Expansion slots: 2 M.2 (1 for SSD, 1 for WLAN)		 	
		Webcam: 5 MP-IR privacy camera			
		Audio Features: Audio by B&O Dual 4 W speakers		1	
		Sound Mixer			
		Channels: 22			
		Ghost Preamps: 16			
		Sapphyre EQ: 4-band (2 bands of swept mids)			
		Limiters on inputs: 8			
		Effects: Dual Engine			
		USB Interface: 2-in/2-out (24-in/22-out on 22 MTK)			
		Auxes: 5			
		Subgroups: 4 mono/2 stereo			
		Faders: 100mm			
		2 units Podcast Microphone			
		Form Factor: Desktop			
		Sound Field: Mono			
		Capsule: 1 x Dynamic			
		Polar Pattern: Unidirectional			
		Orientation: End Address			
		Circuitry: Solid-State			
		High-Pass Filter: None			
		On-Board Controls: Gain, Headphone Volume, -			
		Mic Mute			
		Windscreen: Built-In			
		Frequency Range: 50 Hz to 16 kHz			

·. (,			
	Maximum SPL: Unidirectional: 132 dB SPL •		
I	Impedance: Unidirectional: 314 Ohms at 1 kHz		
	Sensitivity: Unidirectional: -55 dBV at 1 kHz		
	Unidirectional: -47 dBFS/Pa at 1 kHz /		
	A/D Conversion: 16 / 24-Bit		
	Sample Rate: 44.1 / 48 kHz		
	Digital Signal Processing: None		<u> </u>
	Operating System Support: Android, Windows,		
	iOS, macOS/OS X .		ļ
\vdash	Mobile Device Compatibility: iPad or Later,		
	iPhone 6th Gen. or Later, iPod RAM Requirement: 2 GB Minimum		
	Bus Power: USB / Lightning		
	Color: Black		
	Mounting: 5/8"-27 Female		
	Construction Material: Metal		
	2 units Vocal Microphones		
	Frequency Response from: 50 Hz		
	Frequency Response to: 15 KHz		
	Sensitivity (dBV/Pa): -54.5 dBV/Pa		
	Sensitivity (mV/Pa): 1.88 mV/Pa		
<u> </u>	Polar Pattern: Cardioid		
<u> </u>	Transducer Type: Dynamic		
<u> </u>	2 units Stiege-Land Daniel A	_	ļ
	2 units Microphone Boom Arm HEAVY DUTY MIC ARM MICROPHONE STAND		
	SUSPENSION SCISSOR BOOM STANDS		
	BUILT IN SPRING ARM		
	BOILT IN SPAING ARM	-	
ļ. 	2 units Microphone Stand		<u> </u>
	Boom microphone stand with folding tripod base		-
 	Twist-style clutch for vertical height adjustments.		
	30" boom with adjustable length and angle settings.		<u> </u>
	Included cable clip		
	Steel construction.		
			<u> </u>
	3 units Microphone Holder /		
	Large Rubber Mic Clip for Wireless Microphones		
	2 units Professional Studio Headphones ,		
	Transducer Type : Dynamic, Neodym-Magnet		
ļļ	Driver size: 40	 	
	Impedance: 44 Sensitivity: 105 dB SPL/mW		
	Max. Input Power: 500 mW		ļ
	Frequency Range: 10 Hz - 22 kHz		
	Cable length: 3 m		1
	Cable type: Detachable, coiled	1	
	Plug: Gold-plated 3.5 mm stereo mini plug		
	1 unit FULL HD PTZ CAMERA 20X 30X POE NDI		
	1/2.8" HD CMOS Sensor, 20X/30X Optical Zoom >		
	HDMI & 3G-SDI Video Output, PoE Power		
	RS-232/RS-485 Serial Control, Cascading		
	Streaming Protocols: RTSP, RTMP, SRT & NDIHX		<u> </u>
ļ	Control Protocols: Onvif, VISCA over IP,		ļ
. '	VISCA, PELCO-D/P		
	Tripod, Wall & Ceiling Mounting		
			1
	A unit Designation time of our town of	_	
	1 unit Professional IP & Serial PTZ Camera Joystick		
	Controller		
	Controller Control up to 255 PTZ Cameras		
	Controller Control up to 255 PTZ Cameras Control and cross-mix control up to 255		
	Controller Control up to 255 PTZ Cameras Control and cross-mix control up to 255 AVMATRIX cameras or other VISCA-over-IP		
	Controller Control up to 255 PTZ Cameras Control and cross-mix control up to 255 AVMATRIX cameras or other VISCA-over-IP PTZ cameras		
	Controller Control up to 255 PTZ Cameras Control and cross-mix control up to 255 AVMATRIX cameras or other VISCA-over-IP		
	Controller Control up to 255 PTZ Cameras Control and cross-mix control up to 255 AVMATRIX cameras or other VISCA-over-IP PTZ cameras Automatically searches IP network for available cameras		
	Controller Control up to 255 PTZ Cameras Control and cross-mix control up to 255 AVMATRIX cameras or other VISCA-over-IP PTZ cameras Automatically searches IP network for available cameras 4D Joystick		
	Controller Control up to 255 PTZ Cameras Control and cross-mix control up to 255 AVMATRIX cameras or other VISCA-over-IP PTZ cameras Automatically searches IP network for available cameras		
	Controller Control up to 255 PTZ Cameras Control and cross-mix control up to 255 AVMATRIX cameras or other VISCA-over-IP PTZ cameras Automatically searches IP network for available cameras 4D Joystick 4D joystick offers simultaneous pan, tilt, zoom, and focus control		
	Controller Control up to 255 PTZ Cameras Control and cross-mix control up to 255 AVMATRIX cameras or other VISCA-over-IP PTZ cameras Automatically searches IP network for available cameras 4D Joystick 4D joystick offers simultaneous pan, tilt, zoom,		
	Controller Control up to 255 PTZ Cameras Control and cross-mix control up to 255 AVMATRIX cameras or other VISCA-over-IP PTZ cameras Automatically searches IP network for available cameras 4D Joystick 4D joystick offers simultaneous pan, tilt, zoom, and focus control Infinitely variable joystick speed control		
	Controller Control up to 255 PTZ Cameras Control and cross-mix control up to 255 AVMATRIX cameras or other VISCA-over-IP PTZ cameras Automatically searches IP network for available cameras 4D Joystick 4D joystick offers simultaneous pan, tilt, zoom, and focus control Infinitely variable joystick speed control Quick Controls		
	Controller Control up to 255 PTZ Cameras Control and cross-mix control up to 255 AVMATRIX cameras or other VISCA-over-IP PTZ cameras Automatically searches IP network for available cameras 4D Joystick 4D joystick offers simultaneous pan, tilt, zoom, and focus control Infinitely variable joystick speed control Quick Controls Tactile feel with zoom rocker switch		
	Controller Control up to 255 PTZ Cameras Control and cross-mix control up to 255 AVMATRIX cameras or other VISCA-over-IP PTZ cameras Automatically searches IP network for available cameras 4D Joystick 4D joystick offers simultaneous pan, tilt, zoom, and focus control Infinitely variable joystick speed control Quick Controls Tactile feel with zoom rocker switch Quick button/knob control of exposure, shutter		
	Controller Control up to 255 PTZ Cameras Control and cross-mix control up to 255 AVMATRIX cameras or other VISCA-over-IP PTZ cameras Automatically searches IP network for available cameras 4D Joystick 4D joystick offers simultaneous pan, tilt, zoom, and focus control Infinitely variable joystick speed control Quick Controls Tactile feel with zoom rocker switch Quick button/knob control of exposure, shutter speed, iris, white balance, focus, pan/tilt/zoom		

Hardware and Power PoE support and 12 VDC power supply Metal housing 2.2" LCD screen 🕜 Studio Light 600Ws 3x 200Ws Strobe Studio Flash Light Kit with AT-16 Trigger + 3x Softbox + 3x 200cm Light Stand + Reflector + Boo Arm 1 unit Analog Amplifier 2 Channel 700W x 2 at 8 ohms, 1300W X 2 at 4 ohms 5 Mic Input, USB/SD Port, Bluetooth Music, Mic Volume Independently Control Digital Echo Delay & Repeat Control -Kinds of Output: Rec Out. Line Out 🔑 Built-in 4" Fan 1 unit Professional PA Speaker 15" 2-WAY SPEAKER SYSTEM WATTS: 400W SENSITIVITY: 94dB IMPEDANCE: 8ohms 1 unit Video Capture Card 🕝 4K Video Capture Card 1080P 60fps HD Camera Recording Box HDMI - Compatible for Live Streaming -2 units HDMI Cable (10m) 50 units Acoustic Foam Inclusion with assembly/installation with at least 1 year warranty with after sales services with training Item No. Item No. Brand and Model: Delivery Period: Warranty: Price Validity: $After having \ carefully \ read \ and \ accepted \ your \ General \ Conditions, I/We \ quote \ on \ the \ item \ at \ prices \ noted \ above.$ Printed Name / Signature Tel. No. / Cellphone No. e-mail address Date