



Republic of the Philippines
BULACAN AGRICULTURAL STATE COLLEGE
REQUEST FOR QUOTATION

Document No.: BASC-PRO-QSF-02
 Rev. No.: 00
 Effectivity Date: 06/03/2019

Project Reference Number:
 Name of the Project:
 Location of the Project:

Date: _____
 Quotation No. _____

Company Name _____
 Address _____

Please quote your lowest price on the item/s listed below, subject to the General Conditions on the last page, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than _____ in the return envelope attached herewith.

MANDY D. BERNARDO
 Procurement Officer

- NOTE:
1. THE APPROVED BUDGET FOR THE CONTRACT IS _____.
 2. ALL ENTRIES MUST BE TYPEWRITTEN.
 3. DELIVERY PERIOD WITHIN _____ CALENDAR DAYS.
 4. WARRANTY SHALL BE FOR A PERIOD OF three (3) MONTHS FOR NON-EXPENDABLE SUPPLIES ONE (1) YEAR NON-EXPENDABLE SUPPLIES FROM DATE ACCEPTANCE BY THE PROCURRING ENTITY.
 5. PRICE VALIDITY SHALL BE FOR A PERIOD OF _____ CALENDAR DAYS.
 6. PHILGEPS REGISTRATION CERTIFICATE SHALL BE ATTACHED UPON SUBMISSION OF THE QUOTATION.
 7. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATION OF THE PRODUCT BEING OFFERED.

ITEM No.	Unit	ITEM & DESCRIPTION	QTY	UNIT PRICE	TOTAL
1	Lot	Analytical Balance	2		
		Adjustment: External			
		Anti-Theft Locking Device: Kensington Lock, lockdown			
		Application Programs:			
		Weighing, Dosing, Counting, Percentage			
		weighing, Net total, Totalizing, Animal			
		weighing, Calculation, Density, Statistics,			
		Peakhold, Checkweighing, Mass unit			
		conversion and Underfloor weighing			
		Draft Shield: Manual			
		Leveling: Manual			
		Linearity: 0.2 mg			
		Relative humidity at temperatures up to 31° C, non-condensing, then linear decrease from max. 80 % at 31° C to max. 50 % at 40° C: 15 – 80 %			
		Operating Conditions – Temperature: +10 – +30°C			
		Repeatability: 0.1 mg			
		Sensitivity Drift between +10 °C and +30 °C: ±1.5 ppm/K			
		Typical Stabilization Time: ≤1.0 s			
		Underfloor Weighing: Yes			
		Weighing Chamber Height: 240 mm			
		Display: LED screen with touch technology			
		Maximum Weighing Capacity: 220 g			
		Readability: 0.1 mg			
		Weighing Pan Dimensions: ø 120 mm			
		Data Interface: RS232			
		Weighing Units: Gram, kilogram, carat, pound,ounce, troy ounce, Hong Kong tael, Singapore tael, Taiwan tael, grain, pennyweights, milligram,parts per pound, China tael, mommes, Austrian carat, tola, baht, mesghal and Newton			
		<i>Inclusions:</i>			
		<i>Delivery on Site</i>			
		<i>Training with end Users</i>			
		<i>Commissioning and Installation on sites</i>			
		<i>Training Certificate to End Users</i>			
		<i>Calibration Certificate and sticker</i>			
		<i>Certificate of Distributorship from Manufacturer</i>			
		<i>AVR, 1KVA</i>			
		<i>with at least 1 year warranty</i>			
		<i>with after sales services</i>			
2	pc	Emergency Eye Wash Station with Shower Combination	2		
		Preferred Color: Silver			
		Material: Stainless steel			
		Water Inlet Size: DN32 & DN15			
		Water Outlet Size: DN32			
		Working pressure: 0.2-0.4MPa			
		Flowing rate: Shower Head: 12-18L/Min			

		Eyewash flow rate: 1.5L/min		
		Size: 65×33×20cm		
		Weight: 11kg		
		Features:		
		1.The hand-push board is luminous, easy to use at night. Once you push the board in the clockwise direction, the nozzle release water		
		2.Can provide emergency eye/face washing service for more than 15 minutes. The eyewash nozzle has a built-in double-layer filter to filter impurities in the water, provide a comfortable foamy water column.		
		3.High-quality S304 stainless steel outdoor special ABS powder electrostatic spraying, using multilayer polishing process, smooth surface, easy to maintain.		
		Inclusion		
		Installation from the source of the Laboratory water supply		
		install all necessary tubulation, piping and gate valves including civil works		
		Delivery on Site		
		with at least 1 year warranty		
		with after sales services		
		with training		
3	pc	Thermal Imaging Camera	2	
		IR resolution (Pixels): 320×240		
		Display: 3.5" IPS (640×480)		
		Spectral range: 8µm -minimum		
		Focus: Free focus		
		Temperature measurement range: - 40°Cto 400°C		
		Accuracy: ±2%		
		Emissivity: 0.01 to 1.00 adjustable		
		Color palettes: minimum of 6		
		Image modes: 4 minimum		
		Digital camera resolution: 2MP minimum		
		Digital zoom: 2x, 4x		
		Hi/Lo temperature alarm: Icon, LED flashlight		
		Software connectivity: computer with software		
		Battery: Detachable Liion battery pack		
		Battery operation time: ≥ 3 hours		
		USB: Type-C		
		IP rating: IP54		
		Drop proof: 2m minimum		
		Storage: 16G Micro SD card		
		• Image/Video storage format: JPEG or PNG		
		Inclusion		
		with assembly/installation		
		with at least 1 year warranty		
		with after sales services		
		with training		

	Item No.		Item No.
Brand and Model:	_____	_____	_____
Delivery Period:	_____	_____	_____
Warranty:	_____	_____	_____
Price Validity:	_____	_____	_____

After having carefully read and accepted your General Conditions, I/We quote on the item at prices noted above.

Printed Name / Signature

Tel. No. / Cellphone No.
e-mail address

Date