-

A CONTRACT OF THE	Republic of the Philippines	Document No.: BASC-PRO-QSF-02		
	BULACAN AGRICULTURAL STATE COLLEGE	Rev. No.: 00		
The iss and	REQUEST FOR QUOTATION	Effectivity Date: 06/03/2019		
Project Reference	e Number:			
Name of the Pro	ject:			
Location of the H	Project:			

Date: Quotation No. \_

Company Name Address

NOTE:

ITEM No.

1

Please quote your lowest price on the item/s listed below, subject to the General Conditions on the

last page, stating the shortest time of delivery and sumbit your quotation duly signed by your representative not later than \_ in the return envelope attached herewith.

MANDY D. BERNARDO Procurement Officer 1. THE APPROVED BUDGET FOR THE CONTRACT IS \_\_\_\_\_ 2. ALL ENTRIES MUST BE TYPEWRITTEN. 3. DELIVERY PERIOD WITHIN \_\_\_\_\_ CALENDAR DAYS. 4. WARRANTY SHALL BE FOR A PERIOD OF three (3) MONTHS FOR NON-EXPENDABLE SUPPLIES ONE (1) YEAR NON-EXPENDABLE SUPPLIES FROM DATE ACCEPTANCE BY THE PROCURRING ENTITY. 5. PRICE VALIDITY SHALL BE FOR A PERIOD OF \_\_\_\_ \_ CALENDAR DAYS. 6. PHILGEPS REGISTRATION CERTIFICATE SHALL BE ATTACHED UPON SUBMISSION OF THE QUOTATION. 7. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATION OF THE PRODUCT BEING OFFERED. **ITEM & DESCRIPTION** Unit QTY UNIT PRICE TOTAL Spectrophotometer pc 2 Optical System Optical double beam system Wavelength range 100 - 1200 nm Spectral bandwidth 0.5 - 6.0 nm Wavelength accuracy ±0.3nm - ±0.5nm Wavelength reproducibility ≤0.1nm Photometric Range 0.00 - 200.0 (%T) -4.0 - 4.0 (A) pc COLORIMETER Optical Geometry: 45°/0° or 8°/D Sensor: Silicon Photoelectric Diode Array Measuring Aperture: ø4mm - ø20mm Color Space: CIE LAB, XYZ LCh 

-		
1		
	1	

Calibration:



· F

13	Republic of the Philippines	Document No.: BASC-PRO-QSF-02		
to col	BULACAN AGRICULTURAL STATE COLLEGE	Rev. No.: 00		
0f	REQUEST FOR QUOTATION	Effectivity Date: 06/03/2019		

ITEM No.	Unit	ITEM & DESCRIPTION	QTY	UNIT PRICE	TOTAL
		External Calibration			
		Interface			
		RS232 or/with USB			
		Pan size			
		ø90 - ø100			
		Heating Source			
		Halogen Lamp			
		Temperature Sensor			
		PT100			
		Temperature Range			
		40°C - 200°C (1°C Temp. Step)			
		Moisture Range			
		0 - 100%			
		Moisture Readability			
		0.10% - 0.01%			
		Dry/ing Range		1	
		100% - 0%			
		Dry Readability			
		0.10% - 0.01%			
		Time Settings:			
		1min - 99min (by 5s / 10s)			
		Storage:		++	
		15 - 20		+	
4					
4	рс	ANALYTICAL BALANCE	2	++	
		Calibration / Leveling: Manual or Automatic	_		
		Linearity: 0.1mg - 0.2mg			
		Repeatability: 0.1mg - 0.2mg			
		Readability: 0.1mg			
		Capacity: 200g - 220g			
		Pan Size / Dimensions: 80 - 100mm			
		Display: LCD or LED Touch Screen			
		Interface: RS232			
		Adjustment: internal			
		Stabilization Time: 1s - 2s			
		Weighing Units: gram, miligram, and others			
		rated voltage 230			
		with 1KVA AVR			
		Certificate of Distributorship from Manufacturer			
		Calibration Certificate and sticker			
		Inclusions to all equipment		++	
		Delivery, Installation / Assembly			
		Training how to use and maintain the equipment			
		Training Certificate to end users			

Item No.

Item No.

Warranty:

Brand and Mode Delivery Period:

Printed Name / Signature

Tel. No. / Cellphone No. e-mail address

Date