	Republic of the Philippines	Document No.: BASC-PRO-QSF-02
	BULACAN AGRICULTURAL STATE COLLEGE	Rev. No.: 00
	REQUEST FOR QUOTATION	Effectivity Date: 06/03/2019

Project Reference Number:
Name of the Project:
Location of the Project:

Date:
Quotation No. _____

Company Name _____
Address _____

Please quote your lowest price on the item/s listed below, subject to the General Conditions on the last page, stating the shortest time of delivery and sumbit your quotation duly signed by your representative not later than _____ in the return envelope attached herewith.

MANDY D. BERNARDO
Procurement Officer

NOTE:
1. THE APPROVED BUDGET FOR THE CONTRACT IS _____.
2. ALL ENTRIES MUST BE TYPEWRITTEN.
3. DELIVERY PERIOD WITHIN _____ CALENDAR DAYS.
4. WARRANTY SHALL BE FOR A PERIOD OF three (3) MONTHS FOR NON-EXPENDABLE SUPPLIES ONE (1) YEAR NON-EXPENDABLE SUPPLIES FROM DATE ACCEPTANCE BY THE PROCURRING ENTITY.
5. PRICE VALIDITY SHALL BE FOR A PERIOD OF _____ CALENDAR DAYS.
6. PHILGEPS REGISTRATION CERTIFICATE SHALL BE ATTACHED UPON SUBMISSION OF THE QUOTATION.
7. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATION OF THE PRODUCT BEING OFFERED.

ITEM No.	Unit	ITEM & DESCRIPTION	QTY	UNIT PRICE	TOTAL
1	Lot	**SMARTGATE (TURNSTILE)** **TRUSTILE / SWING BEARER** TURNSTILE / SWING BARRIER Servo motor with 1.5 mm SUS304 stainless-steel housing. Acrylic, stainless-steel pipe, or tempered-glass barriers, depending on configuration. Passage width: 550–1,100 mm, depending on configuration. Throughput: approximately 30–60 persons/minute. 14 pairs of infrared sensors, permission validation, anti-tailgating, passage timeout, and LED direction indicators. Includes access controller and fire-alarm input. Connectivity: 10/100 Mbps Ethernet and ISAPI. Power: 100–240 VAC, 50/60 Hz; 55 W per lane. Protection: IP34. Pedestal dimensions: approximately 1,500 × 130 × 1,000 mm. **FACIAL RECOGNITION TERMINAL** 7-inch touchscreen with 2 MP dual-lens camera. Stores 100,000 faces, 500,000 cards, and 150,000 events. Face and smart-card authentication supporting M1, DESFire, and FeliCa, with anti-spoofing. Recognition range: 0.3–3 m; manufacturer-rated speed: below 0.2 seconds/person. Gigabit Ethernet and 2.4 GHz Wi-Fi, with RS-485/OSDP, Wiegand, lock and alarm interfaces. Supports ISAPI, ISUP 5.0, and Push SDK integration. Power: 12–24 VDC, 2 A; protection: IP65. Dimensions: approximately 110.5 × 209.2 × 24 mm.	1		-
					-

	Item No.		Item No.
Brand and Mode	_____	_____	_____
Delivery Period:	_____	_____	_____
Warranty:	_____	_____	_____
Price Validity:	_____	_____	_____

After having carefully read and accepted your General Conditions, I/We quote on the item at prices noted above.

_____
Printed Name / Signature

_____
Tel. No. / Cellphone No.
e-mail address

_____
Date